Application No. 09/676,402
Reply to Office Action of June 4, 2004   - 3 -

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

Listing of Claims:

1. – 17 (Cancelled herein)

18. (Amended herein) A method of evaluating a tentative location for a fixed subscriber

communication site of a wireless communication system using a wireless testing system,

said wireless testing system comprising ~~an antenna positionable at said location for said~~

~~fixed subscriber communication site~~ a testing antenna for communicating ~~said~~ wireless

communication signals with ~~said~~ a transmit antenna and a receive antenna at a base

station, an adjustable mount associated with said testing antenna for orienting said testing

antenna in a plurality of pan orientations and a plurality of tilt orientations, an adjustable

boom attached to said adjustable mount for positioning said testing antenna at a plurality

of heights, a signal measuring device associated with said testing antenna and a signal

attenuator associated with said testing antenna, said method comprising:

~~at said location, positioning said antenna at a set height of said plurality of heights, at a~~

~~set pan orientation of said plurality of pan orientations and at a set tilt orientation of said~~

~~plurality of tilt orientations;~~

at said tentative location

a) positioning said testing antenna such that an angle α defined by said

testing antenna as a vertex between said transmit and receive antennae is

1.5 degrees or less;

McCarthy Tétrault LLP TDO-RED #8243077 v. 1

~~evaluating characteristics~~b) adjusting tilt, pan, and height of said testing

antenna to exchange wireless communication signals ~~transmitted by said~~

~~base station and received by said signal measuring device;~~with said

transmit and receive antennae; and

c) measuring a characteristic of said wireless communication signals

received by said testing antenna by integrating a power signal of said

wireless communication signals across a frequency band associated with

said wireless communication signals:

d) attenuating said wireless communication signals until said ~~signal~~

~~measuring device~~ testing antenna no longer receives said wireless

communication signals ~~transmitted by~~ from said ~~base station~~ transmit

antenna;

e) calculating ambient atmospheric and meteorological conditions

corresponding to said amount of attenuation based on ~~the~~ a distance

between said testing antenna and said base station; and

f) comparing said calculations of said ambient atmospheric and

meteorological conditions to a predetermined threshold level required to

maintain a level of service required for communications with said base

station when said ambient atmospheric and meteorological conditions

exist;

wherein, if said level of attenuation exceeds said threshold level, said ~~antenna placement~~

~~at~~ tentative location for said fixed subscriber communication site is acceptable.

McCarthy Tétrault LLP TDO-RED #8243077 v. 1

Application No. 09/676,402
Reply to Office Action of June 4, 2004   - 5 -

19. - 25. (Cancelled herein)

26. (Amended herein) A method of establishing an optimal location for a fixed

subscriber communication site for a base station having a transmit antenna and a receive

antenna, comprising~:

         at ~~each of a plurality of~~ a tentative ~~locations:~~ location for said fixed subscriber

communication site

                 a) ~~placing a wireless testing system comprised of an antenna and a~~

~~communication unit;~~positioning a testing antenna such that an angle α

defined by said testing antenna as a vertex between said transmit and said

receive antennae is 1.5 degrees or less;

                 b) adjusting tilt, pan, and height of said testing antenna to exchange

wireless communication signals ~~between each of~~ with said ~~plurality of~~

~~tentative locations~~ transmit and said ~~base station;~~ receive antennae; and

                 c) ~~for each tentative location,~~ measuring a characteristic of said wireless

communication signals with said communication unit, ~~; and~~

        ~~d) selecting one of said plurality of tentative locations as said optimal location if~~

~~said characteristic thereof is better than the characteristics measured in all other~~

~~tentative locations.~~

27. (Amended herein) The method of establishing an optimal location for a fixed

subscriber communication site, as claimed in claim 26 wherein

         ~~said characteristic is the power of said wireless communication signals integrated~~

~~over the frequency band associated with said wireless communication signals.~~

McCarthy Tétrault LLP TDO-RED #8243077 v. 1

said testing antenna, receive antenna and transmit are located relative to each

other to form a right angle triangle;

tan α is less than or equal to a ratio comprising

a numerator comprising a distance from said receive antenna to said

transmit antenna; and

a denominator comprising a distance from said testing antenna to one of

said receive antenna and said transmit antenna.

28. (Amended herein) The method as claimed in claim 26, further comprising

establishing an optimal spot for said antenna at each of said plurality of tentative

locations 27, wherein said characteristic is power of said wireless communication signals

integrated over a frequency band associated with said wireless communication signals.

29. (Amended herein) The method as claimed in claim 28, wherein said step of

establishing an optimal spot comprises: further comprising

attenuating said wireless communication signals until said testing antenna

receives practically none of said wireless communication signals transmitted by

said base station;

determining calculating ambient atmospheric and meteorological conditions

corresponding to said amount of attenuation based on a distance d between each

of said plurality of tentative locations and said testing antenna and said base

station; and

~~determining an offset 1 between a location of transmit and receive antennae at said base station; and~~

~~adjusting positioning of said antenna based on receive and transmit signal strengths measured by said communication unit, whenever an angle α provided by tan α = 1 / d is greater than 1.5°.~~

comparing said ambient atmospheric and meteorological conditions to a predetermined threshold level required to maintain a level of service required for said testing antenna to communicate with said base station when said ambient atmospheric and meteorological conditions are present between said base station and said testing antenna.

30. (New) The method as claimed in claim 26, further comprising

repeating steps a), b) and c) at second location;

comparing characteristics measured at said tentative location and said second location; and

selecting one of said tentative location and said second location as said optimal location based on said step of comparing characteristics.

31. (New) The method as claimed in claim 26, further comprising variably attenuating said wireless communication signals before evaluating said characteristics of said wireless communication signals to simulate ambient atmospheric and meteorological conditions around said wireless testing system.